

Redexim 

VERTI-DRAIN


7626



The 7626 is the heaviest and toughest Verti-Drain on the market. It is the ideal machine for the toughest of soil conditions, where a high productivity is needed. It weighs considerably more than the 75-series, and it has a heavier gearbox, PTO and rear roller support. Its adjustments have been made simpler. The tine-depth adjustments are made comfortably from the tractor seat via the hydraulic controls, while the original amount of 'heave' on the tine is left intact.

VERTI-DRAIN 7626

The optional wheel support is constructed extra robustly, while it falls within the 104" (2.6 m) working width of the Verti-Drain. The forward speed is faster than that of the 75-series.



Verti-Drains adjustable parallelogram design shatters the soil, and also allows for clean Coring, on all models.



WORKING SPECIFICATIONS

Working width	104" (2.6 m)
Working depth	up to 16" (40 cm) max.
Tractor speed@500 rev's at PTO	
Spacing 2 1/2" (65 mm)	spacing @ 0.45 mph (0.72 km/h)
Spacing 5" (130mm)	spacing @ 0.90 mph (1.4 km/h)
Spacing 7 1/2" (195mm)	spacing @ 1.35 mph (2.17 km/h)
PTO speed: (max)	up to 500 rpm
Weight	4,254 lbs. (1,930 kg)
Hole spacing side-to-side	2 1/2" (663 mm) with 1/2" (12 mm) tines 5" (127 mm) with 1" (25 mm) tines
Recommended tractor size	7626 - 65 hp, lift cap. 5,070 lbs (2,299 kg) 7626H - 55 hp - double acting hydraulic connection is required
Capacity (maximum)	
Spacing 2 1/2" (65mm)	20,989 sq ft/hr (1,950 sq m/hr)
Spacing 5" (130mm)	41,979 sq ft/hr (3,900 sq m/hr)
Spacing 7 1/2" (195mm)	62,969 sq ft/hr (5,850 sq m/hr)
Standard Tines	3/4" x 16" (19 mm x 406mm) solid
Three point linkage	Cat 2
Accessories available	Hydraulic Wheel Kit 1/2" (12 mm) & 3/4" (19mm) turf hold down kits

FEATURES / BENEFITS

FEATURE	BENEFIT
hydraulic depth adjustment	no need to leave the tractor seat
104" (2.6 m) working width	high productivity
weighs 4,254 lbs. (1,930 kg)	able to penetrate even in the roughest conditions
heavier gear box, rear roller and PTO	able to withstand the most punishing conditions
optional bogey wheel kit	transfers the weight of the machine off of the tractor



Redexim
190031, Russia, St. Petersburg,
Ulitsa Efimova 4a, Office 548-A
Tel. +7 (812) 441-29-41
Fax. +7 (812) 441-29-41
www.redexim.ru
E-mail: info@redexim.ru