



RINK TOP DRESSER

1210



The 12 series top dressers offer you the widest brush applicator top dresser available with a smooth even spread, over 6 ft. wide. This makes the 1210 body mount spreader ideal for fitting onto your utility vehicle, as its spreading width will be outside the vehicle's wheel width. The 1210 is a trailed unit for use behind any prime mover.

RINK TOP DRESSER 1210

The 1210 is a trailed unit for use behind any prime mover. The four pivoting wheels ensure equal and low ground pressure, even on undulating ground. It is hydraulically powered, either from the prime mover or optional auxiliary tank and pump unit.

The full width continuous loop belt has edge guides to ensure central tracking. The Rink delivery and metering system is designed to ensure smooth, even distribution of all types of top dressing materials, including wet sand. The 12 series dressers are ideal for all golf course applications. The hopper is made of aluminum to avoid rusting.



WORKING SPECIFICATIONS

Length	96 in (2.40 m)
Road Width	81 in (2.03 m)
Height	44 in (1.10 m)
Loading Capacity	1.3 cu yd (1.0 cu m)
Spreading Width	72 in (1.80 m) / Up to 30 ft (9 m) With Optional Spinners
Tire Equipment	4 Swing tires Trelleborg Garden Slick 18 x 9.50 - 8
Tire Pressure	15 psi (1.0 bar)
Speed Limit	19 mph (30 km/h)
Towing Capacity	min 15 HP (20 Kw)
Spreading Amount	Continuously adjustable
Minimum Conveying Capacity Towing Vehicle	3.6 US gal/min (15 l/min)
Hydraulics Required	3.6 gpm/980 psi, 4.6 gpm with spinners

FEATURES / BENEFITS

FEATURE	BENEFIT
Precise metering	Enables fine control over density
Easy belt adjustment	Two tracking guides keep belt centered
Exact spreading widths	For neat and economical operation
Ideal weight distribution	Prevents compaction and damage to turf

Redexim 

Redexim
190031, Russia, St. Petersburg,
Ulitsa Efimova 4a, Office 548-A
Tel: +7 (812) 441-29-41
Fax: +7 (812) 441-29-41
www.redexim.ru
E-mail: info@redexim.ru