



RINK TOP DRESSER

DS800



The Rink DS 800 is a topdresser with dual spinners with a spread pattern variable up to 10 m. The operation of the belt and spinners can be done from the tractor seat, by switching the hydraulic lever. No unnecessary drop of material takes place between stopping and operation, since the material release gate automatically closes when the belt is stopped. The spinner disks have been designed in a way that they will handle wet material very well.

RINK TOP DRESSER DS 800

The Topdresser DS800 is used for spreading small-grained, loose material, such as sand, small granular material or similar products. The spreading equipment of the Topdresser is driven by a gear box with hydraulic motor for conveyor belt and a separate hydraulic motor for each spinner. The number of revolutions of the hydraulic system for the conveyor belt and spinners can be continuously adjusted independently by means of a flow divider. Spreading density or spreading amount can be determined by the tractors speed, spinner speed and conveyor belt speed.



WORKING SPECIFICATIONS

Length	95" (2.40 m)
Width	57" (1.45 m)
Height	40" (1.05 m)
Loading Capacity	1.04 cu yd (0.80 cu m)
Total weight capacity	3,300 lbs (1,500 Kg)
Empty weight	710 lbs (approx. 320 kg)
Spreading width	up to 36' (12 m)
Tire equipment	mounted version(no tires)
Speed Limit	19 mph (30 km/h)
Towing capacity	Min 1,200 Kg (30 HP)
Spreading amount	(2,600 lbs) lift capacity
Hydraulic connected load	continuously adjustable
Min conveying capacity towing vehicle	6 gal/min (25 l/min)
Minimum pressure towing vehicle	1,960 PSI (140 bar)

FEATURES / BENEFITS

FEATURE	BENEFIT
dual spinners	variable spread pattern
hydraulic controls	the belt and spinners can be controlled w/o leaving the tractor seat
automatically closing feed gate	no waste of material
new spinner design	will work with even wet material



Redexim
 190031, Russia, St. Petersburg,
 Ulitsa Efimova 4a, Office 548-A
 Tel: +7 (812) 441-29-41
 Fax: +7 (812) 441-29-41
www.redexim.ru
 E-mail: info@redexim.ru