



VERTI-DRAIN

7621



The 7621 weighs considerably more than the 75-Series, and has a heavier gearbox, PTO and rear roller support. It is the ideal machine for the toughest of soil conditions, where high productivity is needed. Its adjustments have been made simpler. The tine-depth adjustments are made comfortably from the tractor seat via the hydraulic controls, while the original amount of 'heave' action is left intact.

VERTI-DRAIN 7621



Verti-Drains adjustable parallelogram design shatters the soil, and also allows for clean Coring, on all models.



WORKING SPECIFICATIONS

Working width	83" (2.1m)
Working depth	16" (400mm)
Tractor speed@500 rev's at PTO Spacing 2 1/2" (65 mm) Spacing 5" (130mm) Spacing 7 1/2" (195mm)	spacing @ 0.45 mph (0.72 km/h) spacing @ 0.90 mph (1.4 km/h) spacing @ 1.35 mph (2.17 km/h)
PTO speed: (max)	up to 500 rpm
Weight	7621-3450lbs (1565kg) 7621H- 3891lbs (1765kg)
Hole spacing side-to-side	5" (129mm) with 24mm tines 2 1/2" (65mm) with 12mm tines
Recommended tractor size	7621: 55HP, lift cap 2000kg 7621H: 45HP
Capacity (maximum) Spacing 2 1/2" (65mm) Spacing 5" (130mm) Spacing 7 1/2" (195mm)	17,400 sq ft/hr (1620 sq m/hr) 34,800 sq ft/hr (3230 sq m/hr) 52,204 sq ft/hr (4850 sq m/hr)
Standard Tines	3/4" x 16" (19 mm x 406mm) solid
Three point linkage	Cat 2
Accessories available	Hydraulic Wheel Kit 1/2" (12 mm) & 3/4" (19mm) turf hold down kits

FEATURES / BENEFITS

FEATURE	BENEFIT
Hydraulic depth adjustment	No need to leave the tractor seat
Wide working width	High productivity
More robust	Able to penetrate even in the roughest conditions
Heavier gear box, rear roller and PTO	Able to withstand the most punishing conditions
Optional bogey wheel kit	Transfers the weight of the machine off of the tractor



Redexim
190031, Russia, St. Petersburg,
Ulitsa Efimova 4a, Office 548-A
Tel. +7 (812) 441-29-41
Fax. +7 (812) 441-29-41
www.redexim.ru
E-mail: info@redexim.ru