



RINK TOP DRESSER

0
1
0
1



The economical 10 series top dressers are ideal for use with low horse power compact tractors and can be either mounted on a 3-point linkage or trailed on four pivoting high flotation wheels to minimize ground pressure. Both models use the tractor hydraulics to power the guided belt and brush applicator. The Rink delivery system ensures an even spread with all spreading materials, even wet sand.

RINK TOP DRESSER 1010

This unit uses tractor hydraulics to power the permanently, self-aligning conveyor belt, delivering the wet or dry material being spread directly to the brush applicator. The ever-popular 1010 model is trailed and rides on four pivoting flotation wheels.



WORKING SPECIFICATIONS

Length	74" (1.8 m)
Road Width	68" (1.7 m)
Working Width	60" (1.5 m)
Height	51" (1.4 m)
Weight	600 lb (270 Kg)
Capacity	1.3 cu yd (1 m)
Tractor required	16 hp, lift cap 2,600 lbs (1179 kg)
Hydraulics Required	980 psi/3.1 gpm, 4.5 with spinners
Options	Auxilliary tank and pump unit

FEATURES / BENEFITS

FEATURE	BENEFIT
Precise metering	Each model enables fine control over density
Easy belt adjustment	Two tracking guides keep belt centered
Exact spreading widths	For neat and economical operation
Works with wet material	Economic, no need for dry sand
Brush provides accurate scattering of sand	Allows continued use of turf area as top dressing is powered into sword
Ideal weight distribution	Prevents compaction and damage to turf

Redexim 

Redexim
190031, Russia, St. Petersburg,
Ulitsa Efimova 4a, Office 548-A
Tel: +7 (812) 441-29-41
Fax: +7 (812) 441-29-41
www.redexim.ru
E-mail: info@redexim.ru