

Redexim 

# VERTI-DRAIN


3  
F  
F  
7



The high-speed Verti-Drain 71 Series is a winner for both golf courses and sportsfields. The 71 Series Verti-Drains are the fastest deep-tine aerators, running at speeds of up to 2.75 mph.

Improvements include single-point arm adjustment, a stronger tine support system and fewer moving parts. The 7113 can drive 6" (150mm) tines, solid or hollow, at a faster rate than any other aerator, which makes it the perfect machine for high speed runs down sportsfields, fairways and for even shorter work on the greens.

# VERTI-DRAIN 7113



Verti-Drains adjustable parallelogram design shatters the soil, and also allows for clean Coring, on all models.

While it still features the unique, "heave" action, there are many new improvements, including single-point arm adjustment, a stronger tine support system and fewer moving parts.

The 7113 can drive 6" tines, solid or hollow, at a faster rate than any other aerator, which makes it the perfect machine for high speed runs down sportsfields, fairways and for even shorter work on the greens.



## WORKING SPECIFICATIONS

Working width	54" (1.34 m)
Working depth	Up to 6" (150 mm)
Tractor speed@500 rev's at PTO	
Spacing 2 1/8" (65 mm)	Up to 1.25 mph (2.0 km/h)
Spacing 3 1/2" (90 mm)	Up to 2.0 mph (3.2 km/h)
Spacing 5" (125mm)	Up to 2.7 mph (4.3 km/h)
PTO speed: (max)	Up to 500 rpm
Weight	1,145 lbs (520 kg)
Hole spacing side-to-side	2 1/8" (55 mm)
Hole spacing in driving direction	1" - 5" (25 mm - 125 mm)
Recommended tractor size	23 hp, min lift cap - 1,450 lbs (650kg)
Capacity (maximum)	
Spacing 2 1/8" (65 mm)	28,514 sq ft (2,650 sq m)/hour
Spacing 3 1/2" (90 mm)	45,192 sq ft (4,200 sq m)/hour
Spacing 5" (125mm)	61,224 sq ft (5,690 sq m)/hour
Three point linkage	3- point CAT 1
Transmission oil	Life time grease EP 00
Lubrication grease	EP 2

## FEATURES / BENEFITS

FEATURE	BENEFIT
Up to 2.75 mph	Fastest rate ever
Unique adjustable parallelogram forced heave	Shatters compaction in any ground conditions. Versatile with single-point adjustment for optimum results and hollow coring
Sealed bearings not bushings	Long maintenance free life
Simple tine design	Easy to change and cheap to replace
Solid and hollow tines	Versatile
54" (1.34 m) working width	Quicker to finish



Redexim  
190031, Russia, St. Petersburg,  
Ulitsa Efimova 4a, Office 548-A  
Tel. +7 (812) 441-29-41  
Fax. +7 (812) 441-29-41  
www.redexim.ru  
E-mail: info@redexim.ru